

BRETFORD BASICS™ OVERHEAD PROJECTOR CART

OH39

Select the overhead projector cart to organize your next presentation. Adjustable projector well allows you to place the projector at the correct height. Constructed of steel and finished in black powder paint, this mobile cart can be easily used in a variety of rooms.



Made In The USA

Now available with a new and improved 6-outlet power strip!



FEATURES

- 39" height is convenient for standing presentations.
- Folding drop leaves on either side of projector platform measure 11" w x 20-1/4" d.
- Large projector platform measures 17" w x 19-3/4" d.
- Projector shelf has four different heights, adjusting from 29-37-3/4" h.
- Narrow design allows the cart to be easily maneuvered through aisles and hallways.
- Smooth rolling 4" casters, two lock.
- Lower storage shelf holds supplies and reference materials.
- New and improved 6-outlet electrical unit available with built-in cord winder and 20' extension cord. Lets you set up anywhere in the room and still reach an electrical outlet. Electrical units are standard on OH39 "E" models.
- Constructed using an average 30% post-consumer recycled steel content and finished in environmentally friendly powder paint. Steel components are 100% recyclable at the end of the product life cycle. Certified to GREENGUARD Children & Schools Indoor Air Quality standards.
- Made in the USA.

DIMENSIONS

Overall (drop leaves down): 22-1/2" w x 19-3/4" d x 39" h
One drop leaf up: 30-1/2" w x 19-3/4" d x 39" h
Both drop leaves up: 39" w x 19-3/4" d x 39" h
Drop leaf panel: 11" w x 20-1/4" d
Projector platform: 17" w x 19-3/4" d
Bottom shelf: 17" w x 19-3/4" d

COLOR & FINISH

Putty Beige (-PB) or Black (-BK) powder paint

STANDARD EQUIPMENT

Leg assembly (2)
Projector shelf (1)
Drop leaf panels (2)
1" square, plastic caster insert (4)
4" mar-resistant black casters (4)
Lower storage shelf

WEIGHT AND FREIGHT CLASS

OH39 and OH39-BK: 40 lbs., Freight class 85 UPS
OH39E and OH39E-BK: 42.5 lbs., Freight class 85 UPS
Ships ready to assemble in one (1) carton pack



ACCESSORIES

E6 Electrical assembly with 6 grounded outlets, 20 ft. grounded extension cord. [Standard on OH39 "E" models.]

CARTON DIMENSIONS & UPC CODE

22-3/4" w x 36" d x 6-1/4" h
OH39: 0 96633 10002 6
OH39-BK: 0 96633 17699 1
OH39E: 0 96633 10448 2
OH39E-BK: 0 96633 17175 0

MADE IN THE USA

Overhead projector carts are made at Bretford's Chicago area manufacturing facility using union labor.

ENVIRONMENTAL SPECIFICATIONS

Overhead projector carts are constructed with "prime" steel which has a 25% to 35% post-consumer recycled content. All steel components are recyclable at the end of the product life cycle. All overhead projector carts are certified to GREENGUARD Children & Schools Indoor Air Quality standards.

SUGGESTED SPECIFICATIONS

(Fill in quantity) OH39 and OH39-BK Overhead Projector Cart(s) is finished in a Putty Beige or Black powder paint coating that is environmentally safe and is constructed from 18 gauge steel. Features include an overhead projector shelf that can be adjusted from 29"-37-3/4" from the floor in order to accommodate different sizes of overhead projectors. The unit features a one piece, press-formed platform with a 4" wide facing front, 3/4" lip on left and right sides, and 4" back facing that includes two (2) slots for mounting the optional electrical unit. Optional electrical assembly provides six (6) grounded outlets with surge suppression. Includes 20 ft. 3-wire cord and two (2) 3/16" diameter machine screws with wing nuts for attaching unit to the table. OH39 "E" models come standard with 6-outlet electrical assembly. Platform facing sides includes a 3/4" flange into which mounting holes are punched. Four (4) 18 gauge, 1" steel tube legs each have three platform mounting holes located 6" from the top and 2-5/8" center distance between holes to permit the aforementioned platform settings and one drop leaf mounting hole located 1-1/2" from the top of the leg. Platform is mounted to each of the four legs using two 1/2" truss screws. Unit also features two (2) drop leaves made from press-formed 18 gauge steel. Leaf edges are smooth with 1" side lips and front and back facings that form a triangle that graduates from 1" to 3". Unit can be operated with both leaves up, down or with just one leaf up. Drop leaf folding mechanism is two steel 1/4" x 17/16" rivets with rivet caps that attach to the front and back facings of each drop leaf panel and the left and right leg assemblies. A non-adjustable 17" w x 19-3/4" d, 18 gauge steel lower shelf attaches to each of the four legs. Constructed with "prime" steel which contains 25% to 35% post-consumer recycled materials. A 1" square black plastic caster insert is mounted to each leg. Four (4) casters are mar-resistant, black hard rubber and are 4" in diameter. Each caster assembly has ball-bearing swivel capabilities and steel construction. Two (2) casters have locking brakes. Table ships ready to assemble via UPS and comes in one carton pack.



11000 SEYMOUR AVENUE
FRANKLIN PARK, ILLINOIS 60131 USA
TOLL FREE PHONE 800-521-9614
PHONE 847-678-2545
TOLL FREE FAX 800-343-1779
FAX 847-678-0852
WWW.BRETFORD.COM