

BRETFORD BASICS™

HEIGHT ADJUSTABLE PRESENTATION CART

HEIGHT ADJUSTABLE PRESENTATION CART

TC35 supports a projector, laptop, document camera, DVD, and other presentation materials. Locking lower cabinet provides storage for electronics and other equipment.



TC35-BK

FEATURES

- Ideal for presentations and instructional use, cart supports a data projector, notebook computer, document camera, DVD player, and scanner with secure lower storage.
- Pull-out shelves are located on both the left and right sides and are 14"d x 20-3/4"w. Shelves have 2" clearance below the top shelf and height adjust between 26-1/2" and 34-1/2" in 1" increments with the top shelf.
- Locking lower cabinet provides safe storage of electronics and equipment and includes grommet holes for cord management. Cabinet may be equipped with a 6-outlet or 12-outlet electrical unit. 6-outlet electrical unit is included on TC35FF model.
- Top shelf is adjustable from 31" to 39"H in 1" increments.
- Heavy-duty 1" square tubular legs with "W" bracket shelf design for maximum strength.
- All-steel construction with die pressed shelves.
- 4" Quiet-Glide stem casters, two are locking. Each caster is load rated to 115 lbs.
- TC35FF includes a surge protected, 6-outlet electrical assembly with on/off switch and 20' grounded power cord. Electrical unit mounts inside the lower cabinet.
- TC35 series carts feature a steel content with 25% to 35% post-consumer recycled steel and are recyclable at the end of the product life cycle. TC35 series carts also comply with the GREENGUARD Environmental Institute's GREENGUARD Children & Schools Indoor Air Quality standards contributing to points toward Leadership in Energy and Environmental Design (LEED) Certification.
- Proudly made in the U.S.A. using union labor.

DIMENSIONS

TC35 Overall: 32-1/2" w x 24-1/4" d x 31" to 39" h
Storage Cabinet: 32" w x 23-3/4" d x 15-7/8" h
Storage Cabinet Doors: 14" h
Pull Out Shelves: 14" w x 20-3/4" d
Pull Out Shelves to Floor: 26-1/2" to 34-1/2" h
Pull Out Shelves Clearance to Top Shelf: 2" h

PULL OUT SHELF WEIGHT CAPACITY

Shelf Load: 20 lbs.

NOTE: The pull out shelves are designed for use with a notebook computer, projector and like items. Objects over than 20 lbs should not be used on the pull out shelves as it may cause a tip hazard when shelves are extended and potentially cause deformation of the glides.

COLOR & FINISH

Black (-BK) powder paint

WEIGHT, FREIGHT CLASS AND UPC CODE

TC35-BK: 104 lbs., Freight class 70
0 96633 27646 2
TC35FF-BK: 108 lbs., Freight class 70
0 96633 27647 9

Both ship ready to assemble in one (1) carton pack and are available to ship via LTL Truck.

CARTON DIMENSIONS

TC35 & TC35FF: 35" l x 33" w x 9-1/2" d



Shelves pushed in for storage.



ACCESSORIES

ECF6 - 6 Outlet Elec Unit (incl. on FF models) - 0 96633 33683 8
E12 - 12 Outlet Electrical Unit - 0 96633 33685 2

MADE IN THE USA

TC series carts are made at Bretford's Chicago area manufacturing facility using union labor.

ENVIRONMENTAL SPECIFICATIONS

The TC35 series carts are constructed using "prime" steel which has a 25% to 35% post-consumer recycled content and is recyclable at the end of the product life cycle. TC35 series carts are certified to GREENGUARD Children & Schools Indoor Air Quality standards.

CART ASSEMBLY SPECIFICATIONS

TC35 Height Adjustable Technology Carts have one (1) 32-1/2" w x 24-1/4" d, 18-gauge steel top shelf with 20-gauge steel stiffener and open corners so the sides of the shelf do not connect. The upper leg assembly fits flush to the top shelf and attach with a 13-gauge steel "W" bracket design that interlocks the legs and shelves for maximum strength and stability. Upper leg assemblies are 1-1/2" square tubular 18-gauge steel and fit over the lower 1" square tubular 18-gauge steel leg assemblies for height adjustability of the top shelf. Lower leg assemblies form the corners of the lower cabinet and attach to the upper and lower shelves with a 13-gauge steel "W" mounting bracket with 1/4" square head bolts and hex nuts that hold leg securely to table. Perforated 20-gauge steel cabinet side panels mount using the square head bolts that secure the shelves to the legs. Cabinet interior is 32" w x 23-3/4" d x 15-7/8" h, cabinet doors are 14" h. Each lower leg has a hard plastic caster insert mounted in the bottom of the tube. Carts have two (2) 14" w x 20-3/4" d, 18-gauge steel pull-out shelves that extend off the left and right sides. Shelves are height adjustable with the top shelf and may be set from 26-1/2" to 34-1/2" h in 1" increments. There is 2" clearance under the top shelf when pull out shelves are pushed in. Models TC35FF includes a surge and overload protected 6-outlet electrical assembly with on/off switch and 20' 3-wire cord and two (2) 3/16" diameter machine screws with nuts for attaching unit to the back panel of the cabinet. Stem casters are mar-resistant, hard black rubber, 4" in diameter. Each caster assembly has ball bearing swivel capabilities, steel construction and is load rated for 115 lbs each. Two (2) have locking brakes. Finished in Black (-BK) powder paint. Ships knocked down (KD) via truck LTL class 70.

11000 SEYMOUR AVENUE
FRANKLIN PARK, ILLINOIS 60131 USA
TOLL FREE PHONE 800-521-9614
PHONE 847-678-2545
TOLL FREE FAX 800-343-1779
FAX 847-678-0852
WWW.BRETTFORD.COM