

BRETFORD BASICS™

HEIGHT ADJUSTABLE FLAT PANEL CART

HEIGHT ADJUSTABLE PRESENTATION CART

TC35FC supports up to a 42" flat panel monitor with room for a projector, laptop, document camera, DVD, and other presentation materials. Locking lower cabinet provides storage for electronics and other equipment.



TC35FC-BK

FEATURES

- Ideal for presentations and instructional use, cart supports up to a 42" flat panel monitor and provides room for a data projector, notebook computer, document camera, DVD player, and scanner.
- TC35FC includes an aluminum pole and universal mounting bracket for up to a 42" flat panel monitor, 90 lbs maximum. Adjustable mounting arms fit mounting holes from 100 to 700mm wide by 100 to 400mm high and have a forward tilt of 0°, 7.5° or 15°.
- Pull-out shelves are located on both the left and right sides and are 14"d x 20-3/4"w. Shelves have 2" clearance below the top shelf and height adjust between 26-1/2" and 34-1/2" in 1" increments with the top shelf.
- Locking lower cabinet provides safe storage of electronics and equipment and includes grommet holes for cord management. Cabinet may be equipped with a 6-outlet or 12-outlet electrical unit. 6-outlet electrical unit is standard on TC35FCFF model.
- Top shelf is adjustable from 31" to 39"H in 1" increments, flat panel monitor pole height adjusts with the top shelf.
- Heavy-duty 1" square tubular legs with "W" bracket shelf design for maximum strength.
- All-steel construction with die pressed shelves.
- 4" Quiet-Glide stem casters, two are locking. Each caster is load rated to 115 lbs.
- TC35FCFF includes a surge protected, 6-outlet electrical assembly with on/off switch and 20' grounded power cord. Electrical unit mounts inside the lower cabinet.
- TC35FC series carts feature a steel content with 25% to 35% post-consumer recycled steel and an extruded aluminum which has an average of 90% post-consumer recycled content. All steel and aluminum components are recyclable at the end of the product life cycle. TC35FC series carts also comply with the GREENGUARD Environmental Institute's GREENGUARD Children & Schools Indoor Air Quality standards contributing to points toward Leadership in Energy and Environmental Design (LEED) Certification.
- Made in the USA.

DIMENSIONS

TC35FC Overall: 32-1/2" w x 24-1/4" d x 59" to 67" h
Storage Cabinet: 32" w x 23-3/4" d x 15-7/8" h
Storage Cabinet Doors: 14" h
Pull Out Shelves: 14" d x 20-3/4" w
Pull Out Shelves to Floor: 26-1/2" to 34-1/2" h
Pull Out Shelves Clearance to Top Shelf: 2" h
Flat Panel Monitor Pole: 28" h
Flat Panel Mount: 100-700mm (3.94"-27.56") wide
100-400mm (3.94"-15.75") high

PULL OUT SHELF WEIGHT CAPACITY

Shelf Load: 20 lbs.

NOTE: The pull out shelves are designed for use with a notebook computer, projector and like items. Objects over than 20 lbs should not be used on the pull out shelves as it may cause a tip hazard when shelves are extended and potentially cause deformation of the glides.

COLOR & FINISH

Black (-BK) powder paint

WEIGHT, FREIGHT CLASS AND UPC CODE

TC35FC-BK: 134 lbs., Freight class 70
0 96633 27649 3
TC35FCFF-BK: 138 lbs., Freight class 70
0 96633 27648 6

Both ship ready to assemble in one (1) carton pack and are available to ship via LTL Truck.

CARTON DIMENSIONS

TC35FC & TC35FCFF: 35" l x 33" w x 9-1/2" d

ACCESSORIES

FPPSP31 - 31" Speaker Bar, Aluminum - 0 96633 26890 0
ECF6 - 6 Outlet Elec. Unit (incl. on FF models) - 0 96633 33683 8
E12 - 12 Outlet Electrical Unit - 0 96633 33685 2
FPTVULM4 - Monitor Metric M4 Security Screws - 0 96633 31751 6
FPTVULM5 - Monitor Metric M4 Security Screws - 0 96633 31752 3
FPTVULM6 - Monitor Metric M4 Security Screws - 0 96633 31753 0
FPTVULKEY - Metric Security Screw Key - 0 96633 31754 7



MADE IN THE USA

TC series carts are made at Bretford's Chicago area manufacturing facility using union labor.

ENVIRONMENTAL SPECIFICATIONS

The TC35FC series carts are constructed using "prime" steel which has a 25% to 35% post-consumer recycled content and an extruded aluminum which has an average of 90% post-consumer recycled content. All steel and aluminum components are recyclable at the end of the product life cycle. TC35FC series carts are certified to GREENGUARD Children & Schools Indoor Air Quality standards.

MONITOR MOUNTING SPECIFICATIONS

For use with up to a 42" flat panel monitor, 90 lbs. maximum. The monitor assembly has two arms that secure to the mounting holes in the back of the monitor and hang on a horizontal plate that secures to the aluminum pole. Arms are adjustable to fit the mounting hole pattern on the back of the monitor from 100 mm to 700 mm wide and 100 mm to 400 mm high. A transition plate has forward tilt adjustment settings of 0°, 7-1/2° or 15° and is designed to prevent slipping of the monitor's angle when in transit.

CART ASSEMBLY SPECIFICATIONS

TC35FC Height Adjustable Flat Panel Carts have one (1) 32-1/2" w x 24-1/4" d, 18-gauge steel top shelf with 12-gauge steel stiffener, open at the corners so the sides of the shelf do not connect. The upper leg assembly fits flush to the top shelf and attach with a 13-gauge steel "W" bracket design that interlocks the legs and shelves for maximum strength and stability. Upper leg assemblies are 1-1/2" square tubular 18-gauge steel and fit over the lower 1" square tubular 18-gauge steel leg assemblies for height adjustability of the top shelf. Lower leg assemblies form the corners of the lower cabinet and attach to the middle and lower shelves with 13-gauge steel "W" mounting brackets and 1/4" square head bolts and hex nuts that hold leg securely to table. Perforated 20-gauge steel cabinet side panels mount using the square head bolts that secure the shelves to the legs. Cabinet interior is 32" w x 23-3/4" d x 15-7/8" h, cabinet doors are 14" h. Each lower leg has a hard plastic caster insert mounted in the bottom of the tube. Includes a 28" long aluminum pole and mounting bracket assembly for a flat panel monitor up to 42" or 90 lbs. maximum. TC35FC carts have two (2) 14" d x 20-3/4" w, 18-gauge steel pull-out shelves that extend off the left and right sides. Shelves are height adjustable with the top shelf and may be set from 26-1/2" to 34-1/2" h in 1" increments. There is 2" clearance under the top shelf when pull out shelves are pushed in. Model TC35FCFF includes a surge protected 6-outlet electrical assembly with on/off switch and 20' 3-wire cord and two (2) 3/16" diameter machine screws with nuts for attaching unit to the back panel of the cabinet. Stem casters are mar-resistant, hard black rubber, 4" in diameter. Each caster assembly has ball bearing swivel capabilities, steel construction and is load rated for 115 lbs each. Two (2) have locking brakes. Finished in Black (-BK) powder paint. Ships knocked down (KD) via truck LTL class 70.



11000 SEYMOUR AVENUE
FRANKLIN PARK, ILLINOIS 60131 USA
TOLL FREE PHONE 800-521-9614
PHONE 847-678-2545
TOLL FREE FAX 800-343-1779
FAX 847-678-0852
WWW.BRETFORD.COM