

# BRETFORD BASICS™

## TECHGUARD ANTI-THEFT A/V CART

### A26TG42

Bretford's open shelf adjustable security cart is perfect for a variety of applications. Cart includes security cable, Swivel Node Security Points, reprogrammable lock, and Integrated Security Point welded to the top shelf. Adjusts from a minimum height of 26" up to a maximum height of 42". Recommended for use with up to 20" diagonal screen TV's/Monitors.



**Now available with a new and improved 6-outlet power strip!**



### FEATURES

- Includes everything required to secure your data projector, monitor, recorder and/or other audio visual equipment to the cart, all in one package.
- Integrated Security Point (ISP) is welded directly to the cart to provide maximum security against theft.
- Cable security system includes a Grey Mist vinyl coated, 6', heavy duty security cable with stop, three Swivel-Node Security Points that attach directly to your equipment with a heavy duty strength adhesive (adhesive included), a mouse and keyboard cable clamp to secure computer equipment, and a re-programmable combination lock.
- Top shelf is height adjustable from 26"-42" for use while seated or standing and includes a non-slip rubber mat.
- New and improved 6-outlet electrical unit available with built-in cord winder and 20' extension cord. Lets you set up anywhere in the room and still reach an electrical outlet. Electrical units are standard on A26TG42E model.
- Holds a data projector, up to a 20" CRT TV, 24" flat panel, or other audio visual equipment.
- Steel construction finished in a durable Grey Mist powder paint.
- 4" heavy duty industrial grade swivel casters, two with locking brakes.
- Minimal assembly required.
- A26TG42 series carts feature a steel content with 25% to 35% post-consumer recycled steel and are recyclable at the end of the product life cycle. A26TG42 series carts also comply with the GREENGUARD Environmental Institute's GREENGUARD Children & Schools Indoor Air Quality standards contributing to points toward Leadership in Energy and Environmental Design (LEED) Certification.
- Made in the USA.



## DIMENSIONS

Overall: 24" w x 18" d x 26"-42" h

Top Shelf: 24" w x 18" d

Middle to bottom shelf: 15-1/2" h

Vinyl Coated Security Cable: 6' l x 5/16" Dia, (1/4" diameter steel cable)

## COLOR & FINISH

Grey Mist (-GM) powder paint

## STANDARD EQUIPMENT

- (1) 6' vinyl coated steel security cable with stop
  - (3) Swivel Node Security Points with adhesive
  - (1) Mouse and keyboard cable clamp
  - (1) Reprogrammable combination lock
  - (3) 24" w x 18" d Shelves
  - (4) 4" diameter "Quiet Glide" casters, two locking
  - (1) 18" x 24" Rubber Mat
  - (1) 6-outlet electrical unit (1) [A26TG42E model only]
- Plastic bag with all necessary hardware for assembly

## ACCESSORIES

- |          |  |
|----------|--|
| TGLOCK   | Reprogrammable combination lock  |
| 044-0025 | 5" caster pak with 2 locking brakes (use as a substitute for 4" casters) |
| SBRT     | Ratcheted Safety Belt  |

## WEIGHT AND FREIGHT CLASS

A26TG42-GM: 44 lbs., Freight class 85 UPS

A26TG42E-GM: 47 lbs., Freight class 85 UPS

Both ship UPS assembled in one carton pack.

## CARTON DIMENSIONS & UPC CODE

Carton Pack: 23-3/4" w x 20-3/4" d x 26-1/2" h

A26TG42-GM: 0 96633 19877 1

A26TG42E-GM: 0 96633 19843 6

## ENVIRONMENTAL SPECIFICATIONS

Constructed using "prime" steel which has a 25% to 35% post-consumer recycled content and is recyclable at the end of the product life cycle. A26TG42 series carts are certified to GREENGUARD Children & Schools Indoor Air Quality standards.

## MADE IN THE USA

The A26TG42 adjustable security cart is made at Bretford's Chicago area manufacturing facility using union labor.

## SUGGESTED SPECIFICATIONS

20-gauge steel shelves, arc welded to 14-gauge steel legs, with one 12-gauge Integrated Security Point arc welded to the underside of the top shelf. Top leg section 21-1/4" in length, bottom section 19" in length. Security system includes a galvanized 6' steel aircraft security cable which is 1/4" thick and vinyl coated to 5/16" diameter with a 7 x 19 strand. Combination padlock has 40mm diameter loop. Swivel Node Security Points are 50mm diameter and attach with Cyano-acrylate Bonding Adhesive (a 3 gram tube included) to attach nodes. Mouse and keyboard cord clamp is 12-gauge steel. "Quiet Glide" caster system with arc welded caster sockets. Casters are 4" diameter Black hard rubber (2 with locking brakes). Each caster is load rated to accept 115 lbs. Cart has three (3) 20-gauge steel 18" x 24" shelves, each press formed with a 1/4" lip bordering the top surface on all four sides. Top shelf has a 20-gauge steel stiffener electrically welded underneath the surface and a 12-gauge Integrated Security Point welded to the underside. A non-slip black rubber 18" x 24" mat is placed on the top shelf. Top shelf has two (2) 3/16" diameter holes centered on two sides to accept electrical assembly. The cart has an adjustable top section that consists of one (1) 20-gauge 18" x 24" shelf with four (4) 14-gauge steel legs, 21-1/4" long, welded to the shelf at each corner. Offset legs have two (2) 1/4" diameter holes near the bottom of the section and in the center of the leg. The holes are spaced 4" apart to permit height adjustments of 26", 30", 34", 38" and 42" when matched to the bottom section of the table. Each offset leg fits over the bottom section of the table and is secured at the desired height by a 1/4-20 machine screw. The bottom section consists of two (2) 20-gauge steel 18" x 24" shelves - one at the top of the section and the other at the bottom. There are four (4) 14-gauge steel 19" legs welded to the shelves at each corner. Each 19" leg has four (4) 1/4" diameter holes down the center of the leg. Holes are 4" apart to permit height adjustment (noted above). Galvanized security cable is 6' long, 1/4" thick, 7 x 19 strand, and vinyl coated to a 5/16" diameter. Swivel Node Security Points are 50mm diameter coated in Grey Mist powder paint and use a Cyano-acrylic bonding adhesive (included) to attach to equipment. Padlock is reprogrammable and has a 40mm U loop diameter. A plastic caster insert is mounted to each leg. A26TG42E-GM includes an electrical assembly with six (6) grounded outlets. Includes 20', 3-wire power cord and two (2) 3/16" diameter machine screws with wing nuts for attaching unit to the cart. Ships assembled in one (1) carton via United Parcel Service (UPS).



1 - Attach the Swivel Node Security Points (SSP) with adhesive



2 - Slide the security cable through the Integrated Security Point to the stop and then through the SSP's on the equipment you wish to protect



3 - Attach the lock through the end of the security cable



**BRETFORD**

11000 SEYMOUR AVENUE  
FRANKLIN PARK, ILLINOIS 60131 USA  
TOLL FREE PHONE 800-521-9614  
PHONE 847-678-2545  
TOLL FREE FAX 800-343-1779  
FAX 847-678-0852  
WWW.BRETFORD.COM